In Reply to USPTO Correspondence of N/A

Attorney Docket No. 1217-032260

AMENDMENTS TO THE SPECIFICATION

Please <u>delete</u> the section heading beginning at page 1, line 1.

Please <u>delete</u> the section heading beginning at page 4, line 24.

Please replace the paragraph beginning at page 5, line 19, with the following rewritten paragraph:

--Accordingly, it is an object of the present invention to produce an as-grown single crystal of calcium fluoride having a straight barrel part diameter of not-17 cm or more and having small internal strain and sufficiently small birefringence by the single crystal pulling method.--

Please replace the paragraph beginning at page 6, line 3, with the following rewritten paragraph:

--The present inventors have earnestly studied to solve invention solves the above problems. As a result, they first succeeded in by producing a large-sized, as-grown single crystal of calcium fluoride having extremely small birefringence by a single crystal pulling method, and accomplished the present invention.--

Please replace the paragraph which starts on page 6, line 23 and ends on page 7, line 2, with the following rewritten paragraph:

--Fig. 1 is a schematic view of a single crystal pulling apparatus favorably preferably used for producing the as-grown single crystal of calcium fluoride of the present invention.--

Please replace the paragraph beginning at page 13, line 12, with the following rewritten paragraph:

In the single crystal pulling apparatus of Fig. 1, the heat insulating wall 26 is extended to be upward longer than that in the single crystal pulling apparatus used for manufacturing a single crystal of silicon or the like shown in Fig. 2. In addition, the heat insulating wall 26 surrounds (circularly encloses) a whole circumference from a lower end to

Application No. Not Yet Assigned Paper Dated: November 19, 2003 In Reply to USPTO Correspondence of N/A

Attorney Docket No. 1217-032260

an upper end in the crucible 20, and furthermore, surrounds the side peripheral portion of a single crystal pulling region 38 provided thereabove.

Please replace the paragraph beginning at page 15, line 19, with the following rewritten paragraph:

--The pitch type graphite mold heat insulating material is <u>preferably</u> used particularly <u>preferably</u>-because it can achieve a desired coefficient of thermal conductivity and is excellent in a-<u>its</u> resistance to a-<u>the</u> severe environment <u>encountered</u> in the pulling <u>process</u> and a-<u>possesses excellent</u> mechanical strength.--

Please replace the paragraph beginning at page 19, line 5, with the following rewritten paragraph:

--The graphite is <u>preferably</u> used particularly <u>preferably</u>-because it can achieve a desired coefficient of thermal conductivity and is excellent in <u>a-its</u> resistance to <u>a-the</u> severe environment <u>encountered</u> in the pulling <u>process</u> and <u>a-possesses excellent</u> mechanical strength.--

Please replace the section heading on page 29, line 7, with the following section heading:

EXAMPLE EXAMPLES

Please delete the section heading on page 38, line 1.